

Stem Diameter

Wire Gage No.	Wire Diameter	Twisted Wire Diameter Single Stem	Twisted Wire Diameter Double
7	.174 - .180	N/A	N/A
8	.157 - .165	.305 - .320	.405 - .432
10	.130 - .138	.250 - .258	.345 - .349
11	.115 - .124	.228 - .230	.305 - .314
12	.100 - .109	.185 - .206	.268 - .275
13	.085 - .094	.161 - .170	.225 - .235
14	.077 - .083	.145 - .150	.198 - .208
15	.070 - .074	.125 - .135	.185 - .190
16	.060 - .065	.115 - .121	.160 - .170
17	.052 - .056	.100 - .102	.135 - .145
18	.045 - .050	.090 - .092	.120 - .125
19	.039 - .043	N/A	N/A
20	.032 - .037	.630 - .065	N/A
21	.029 - .034	N/A	N/A
22	.0280 - .0295	N/A	N/A
24	.0225 - .0235	N/A	N/A
26	.0175 - .0185	N/A	N/A
30	.0135 - .0145	N/A	N/A
32	.0123 - .0133	N/A	N/A
33	.0113 - .0123	N/A	N/A
36	.0085 - .0095	N/A	N/A
38	.0075 - .0085	N/A	N/A

NOTE: All fill wire from .003” Dia. to .026” Dia. has a tolerance of +/- .0005”.